

# Rubber blade elements

## Purpose:

- -for snowploughs
- -assembly by means of mounting screws

# Place of production:

Poland

### Material:

Vulcanised rubber reinforced with a recycled textile cord



### Dimensions:

	MODEL	WIDTH (mm)	LENGHT (mm)	HEIGHT (mm)	WEIGHT (kg)	Compatible with
	P/I	250	520	50	8	Dobrowolski - plough PO 641
	P/II	175,5	725	50	7,5	Schmidt - plough SNK 270
	P/III	200	522	50	7	DANROB - plough P097
	P/IV	175	450	50	4	Schmidt - plough SNK 300
	P/VI	200	620	50	7	Dobrowolski - plough SNK 300
THE WAY	P/VII	250	3250	40	47	OZAMET OZW 35
	P/VIII	250	3550	40	43	OZAMET OZW 35
	P/IX	200	3250	40	31	OZAMET OZW 35
Service of the servic	PS/I-90	212	900	50	10	Rubber-metal blades
	P5/I-120	212	1200	50	15	Rubber-metal blades

## Colour:

Black

# Technical parameters:

Parameters	Value ≤	Unit	Standard / Method	
Tensile strength	4 80	MPa	PN-ISO 37 PN-EN ISO	
Hardness	(±5) ≥	°ShA	868:2005 PN-ISO	
Abrasion	195 ± 2	cm3	4649 od	
Tolerance - length, width	± 2 ± 2	%	nominalnego od	
Tolerance - height		%	nominalnego od	
Tolerance- weight		%	nominalnego	

TRAFFICMINDS Kft. | Magyarország 2094 Nagykovácsi, Táncsics köz 9.

TIN: 14580835-2-13 | CRN: 13 09 192833

Tel: + 36 30 631 4193

E-mail: trafficminds@trafficminds.hu www.trafficminds.hu



# Technical Specification Nr 4/2022 Issue A/ 06.06.2022

## Packing:

Packed in a cardboard box on a Euro pallet in quantities depending on the order. Description on the pallet with the name of the product, its quantity, batch number and packing date. Other packaging is possible on request

#### Identification:

Product- on the underside of the product information about the date of production.

Pallet- product name, quantity, pallet identification number, packing date, quality control stamp.

### Storage:

The products should be stored on pallets in protective film and protected from external weather conditions.

The products may be stored for a longer period of time only in closed, ventilated rooms without humidity, after removing the protective film. Storage temperature: max 40 oC

## Health, safety and fire conditions:

Conditions for storage and use of the product- must meet all requirements for storage and use of rubber materials.