

Rubbercurb

Purpose:

- banding of traffic islands and traffic circles
- curbs in tunnels and crossings

Place of production:

Poland

Material:

- Vulcanised rubber
- 3M reflective tape
- Metal reinforcements for mounting

Dimensions:

length	1000 mm
width	90 mm
height	100 mm

Weight:

7,0 kg

Colour:

- black/ red
- white 3M reflective tape

**Technical parameters:**

Parameters	Value	Unit	Standard / Method
Tensile strength	$\geq 4,0$	MPa	PN-ISO 37 PN-EN ISO
Hardness	≥ 60	°ShA	868:2005 PN-EN ISO
Water absorption	≤ 2	%	62 of nominal
Tolerance - length, width	± 2	%	of nominal
Tolerance - height	± 2	%	of nominal
Tolerance- weight	± 2	%	

Packing:

Packed in a cardboard box on a Euro pallet, 150 pieces.

Description on the pallet with the name of product, quantity, batch number and packing date.

On customer's request other way of packing possible

Identification:

Product- on the underside of the product information about the date of production.

Pallet- product name, quantity, pallet identification number, packing date, quality control stamp.

Storage:

The products should be stored on pallets in protective film and protected from external weather conditions.

The products may be stored for a longer period of time only in closed, ventilated rooms without humidity, after removing the protective film. Storage temperature: max 40 oC

Health, safety and fire conditions:

Conditions for storage and use of the product- must meet all requirements for storage and use of rubber materials.